



**APPLICATIONS :**

Aircraft, Oil & Gas, Cathodic Protection, Defense & Marine, Waste water treatment, railway, metro, mono rail, telecommunication, Power plant, Automation, Testing lab's & Institutes, Automotive & Metal processing etc.

**KEY FEATURES :**

- CV-CC Mode
- Independent Setting of V & I
- Manual Current Limit option
- Active Current Sharing
- N+1 Redundancy
- Parralable & Seriesable
- High Reliability & Stability
- Endurance Performance
- PC Interface (Optional)

**TECHNICAL SPECIFICATIONS :**

Specifications	PIPL-1510	PIPL-3005	PIPL-6003	PIPL-7502	PIPL-10002
<b>Output Characteristics</b>					
Voltage	0-15V	0-30V	0-60V	0-75V	0-100V
Current	0-10A	0-5A	0-2.5A	0-2A	0-1.5A
Max Power	150W	150W	150W	150W	150W
<b>Input Characteristics</b>					
Input Voltage	180V TO 270VAC (230vac - 1Phase)				
Frequency	47-63Hz				
Efficiency	> 85%				
<b>CV-CC Mode</b>					
Line Regulation	<±0.5%				
Load Regulation	<±0.5%				
Ripple and Noise	1% P-P				
<b>General</b>					
Protection	Over Voltage, Over Load, Short Circuit, Over Temp.,				
Operating Temperature	-5 to 55deg				
IO Isolation	I/P to O/P : 1.5KV & I/P TO GND : 500VDC				
Safety & EMC	Design to meet UL60950-1/ EN55011 / EN55022 & EN61000-4-2				
Cooling	Conventional Fan Cooled				
Dimensions	145 (W) x 210 (D) x 145 (H) mm				

WE PURSUE A POLICY OF CONTINUOUS DEVELOPMENT AND PRODUCT IMPROVEMENT. THUS THE SPECIFICATIONS IN THIS DOCUMENTS AND THE LOCATION OF CONTROLS ON THE FRONT PANEL MAY BE CHANGE D WITHOUT NOTICE.

Nov 2020